

In the Specification

Page 3, the paragraph beginning on line 14, should be changed to:

Frame structure 12 comprises two laterally-spaced side frames 14, 16 connected by cross members 32, 34, 36. Side frame 14 comprises a bottom member 18, front member 22, and back member 26. Side frame 16 comprises bottom member 20, front member 24, and back member 28. Support feet ~~56~~ 30 are attached to the ends of the bottom members 18, 20. Front members 22, 24 extend upwardly at a slight angle from the forward end of respective bottom members 18, 20. Back members 26, 28 extend upwardly from the rearward end of respective bottom members 18, 20 and are joined to the top end of respective front members 22, 24.

Page 6, the paragraph beginning on line 4, should be changed to:

The cable and pulley system 100 further includes a dual sliding pulley and cable assembly 120, shown in Figure 3. The dual sliding pulley and cable assembly 120 comprises first and second movable pulley assemblies 122, 142. The term "movable pulley" as used herein means a pulley with a movable axis. The first movable pulley assembly 122 comprises movable pulleys 124, 126 mounted on a movable carriage 128. Pulley assembly 142 comprises movable pulleys 144, 146 mounted on a movable carriage 148. Carriages 128, 148 slide vertically along respective carriage guides ~~54, 56, respectively~~. Movable pulley assemblies 122, 142 are interconnected such that the position of the pulley assemblies 122, 142 can be adjusted independently of one another.